



Attacco gas
Corrente elettrica
4 piedini regolabili

Order nr	A (mm)	B (mm)	C (mm)	D (mm) -fan / +fan	H (mm)	O (mm)	Gas ø (mm)	Kg	Fresh air m³/h	m³/h natural gas	Gas C°	kW
NI G0	1000	750	260	200	1460	150	18 mm	~110	288	1.15	99°C	5,0-11,0
NI G1	1250	750	260	250	1460	150	18 mm	~125	360	1.40	101°C	5,0-13,0
NI G2	1500	750	260	250	1460	150	22 mm	~145	432	1.70	108°C	6,5-15,6
NI G3	1750	750	260	300	1460	150	22 mm	~160	504	2.00	113°C	6,5-17,0
NI G4	2000	750	260	300	1460	150	22 mm	~175	576	2.30	117°C	7,0-17,8
NI G5	2250	850	310	300 / 300	1610	200	22 mm	~200	648	2.40	119°C	8,4-19,0
NI G6	2500	950	310	350 / 300	1710	200	22 mm	~220	720	2.50	120°C	8,5-22,0
NI G7	3000	1050	310	350 / 300	1810	200	22 mm	~250	864	2.75	121°C	8,5-22,0
NI G8	3500	1150	310	400 / 300	1910	200	22 mm	~300	1008	2.90	121°C	8,5-22,0